

AVIATION SURVIVOR LOCATOR LIGHT

# LNK-AL15

The ACR LNK-AL15 Rescue Light is a reserve battery powered aviation survivor locator light, which is secured to a life jacket or life preserver for the purpose of facilitating location of persons who have survived an emergency at sea. The light is designed and manufactured to meet FAA TSO-C85b and CAAC CTSO-C85b requirements.



**High Efficiency LED Bulb** 



Simple Life Jacket Integration



Ultra Small and Light Weight Design



## **LNK-AL15**

#### WATER ACTIVATED AVIATION SURVIVOR LOCATOR LIGHT

The LNK-AL15 is an FAA approved water-activated LED survivor locator light that is approved for use on life vests or life preservers in order to indicate the location of survivors in water as a result of an aviation related accident.

The lamp and lens combo of the LNK-AL15 produce a powerful light that will last for a minimum of 8 hours after activation with a minimum light intensity of 1 cd. Throughout its entire operational life, the light will continuously output a steady white light to

clearly indicate a survivor's location and increase the probability of rescue.

The LNK-AL15 light is available under three different part numbers which correspond with different wire lengths. The ability to offer multiple wire lengths provides a greater level of flexibility for different installation scenarios. The LNK-AL15 available wire lengths are 9", 18", and 24".



Fresh & Salt Water Activation



Indefinite Battery Storage Life\*



Simple Life Jacket Integration



**Water Activated** 



Ultra Small and Light Weight Design



High Efficiency LED

\*Assuming light does not accidentally come into contact with

water and is stored as per stated storage requirements

### **SPECIFICATIONS**

**Product Number:** 1503023B (9" / 23 cm) | 1503046B (18" / 46 cm) | 1503061B (24" / 61 cm)

Model Number: LNK-AL15

#### **Light Type**

Steady White Light

#### Batterv

Water-activated Reserve Battery

#### Activation Method

Automatic (Water-Activation)

#### **Light Intensity**

Over 1 cd

#### **Activation Time**

Less than 2 minutes in either fresh or salt

#### Operational Time

Minimum of 8 hours

#### **Horizontal Light Angle**

≥300°

#### Storage Humidity

≤80%

#### **Exposed Length of Wire**

9" - 24" (based on specific product number)

#### Weight

28g-31.5g (depending on wire length)

#### **Dimensions**

Battery pack body: 2.55" x 0.82" x 0.36"

(64.9 x 20.8 x 9.2mm) Lamp: 1.50" x 1.06" (φ38.2 x 26.9mm)

#### **Working Temperature**

2°C - 30°C (35.6°F - 86°F)

#### **Storage Temperature**

30°C - 65°C (-22°F - 149°F)

#### Warranty

1 year

#### Vertical Light Angle

≥5°

#### Approvals

• TSO-C85b



## For further information please contact: ACR Electronics, Inc.

5757 Ravenswood Road Fort Lauderdale, FL 33312

www.ACRARTEX.com

Tel: (954) 981.3333 Fax: (954) 983.5087 Email: sales@acrartex.com